



Product Specifications

Construction	Cut and Loop
Backing	Woven Synthetic
Dye Method	Solution Dyed
Fiber Type	PureColor® Nylon
Face Weight	32 oz./sy (1085 grams/m2)
Pile Density	4035 oz./y3 (149.62 kg/m3)
Pattern Repeat	36.00" (w) x 28.00" (l) approx. (91.44cm x 71.12cm) *Economy Match
Gauge	1/8 (3.15 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Living Spaces

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	47.2%
Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



9770 Pinehurst




9785 Cypress P...



9792 Augusta



9832 Pebble Be..



9925 Saw Grass



9945 Glen Abbey



9999 SandHills