

MSI

Making Dream Surfaces Attainable



Eden

Porcelain Collection

www.msisurfaces.com

Size	Thickness	EDEN BARDIGLIO
12x24 Polished	3/8"	NEDEBAR1224P
12x24 Matte	3/8"	NEDEBAR1224
32x32 Polished	3/8"	NEDEBAR3232P
32x32 Matte	3/8"	NEDEBAR3232
24x48 Polished	3/8"	NEDEBAR2448P
24x48 Matte	3/8"	NEDEBAR2448
4x24 Polished	3/8"	NEDEBAR4X24BNP
4x24 Matte	3/8"	NEDEBAR4X24BN
3x3 Matte	3/8"	NEDEBAR3X3HEX
2x2 Matte	3/8"	NEDEBAR2X2HEX

Colors



Eden Bardiglio 12"x24"



Eden Bardiglio 24"x24"

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				III	V3	DCOF < 0.42 Polished DCOF > 0.42 Matte	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Abrasion Resistance	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	III	Resistant	Rectified	Glazed

Acquire the jaw-dropping beauty of natural Edén at a more palatable price point with the porcelain Edén Bardiglio. The rectified ink jet tile is an elegant interpretation of the natural stone that requires virtually no maintenance. The series is available in an impressive array of sizes: 12"x24", 24"x48", 32"x32" and 4"x24" bullnose.

Technical Information

Primary Colors: Grey
Material Type: Porcelain
Finish: Polished & Matte

Features At A Glance

- Luxurious porcelain (Matte and Polished) tiles with authentic marble looks and colorations
- High quality Ink Jet technology

Trim



4" x 24" Bullnose

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

