


MSI

Making Dream Surfaces Attainable



Focus

Porcelain Collection

www.msisurfaces.com

Colors



Glacier 12"x24"



Graphite 12"x24"

Size	Thickness	GLACIER	GRAPHITE
12x24	3/8"	NFOCGLA1224-N	NFOCGRA1224-N
2x2	3/8"	NFOCGLA2X2-N	NFOCGRA2X2-N
3X18	3/8"	NFOCGLA3X18BN-R	NFOCGRA3X18BN-R

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				III	V2	SCOF - > 0.60 Wet DCOF - < 0.42 Wet	> 275 lbf	< 0.5%	5
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

Designers of fashion and interiors can’t seem to get enough of mixing and harmonizing with pattern. Translate the trend to floors and walls with the Focus series. Thin directional stripes make a contemporary statement in rectified porcelain. The 12"x24" inch tiles come in Glacier and Graphite and mix and match beautifully with the Dimensions and Loft series.

Technical Information

Primary Colors: Beige, Gray
Material Type: Glazed Porcelain
Finish: Matte

Features At A Glance

- Contemporary Fabric Look
- Glazed Porcelain
- Rotocolor Printing
- Rectified for Precision Installation

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

Trim



3" x 18" Bullnose

