

MSI

Making Dream Surfaces Attainable



Metropolis
Porcelain Collection

www.msisurfaces.com

Colors



Avorio 12"x24"



Cloud 12"x24"



Gray 12"x24"



Taupe 12"x24"

Size	Thickness	AVORIO	CLOUD	GRAY	TAUPE
12x24	3/8"	NMETAVO1224	NMETCLO1224	NMETGRA1224	NMETTAU1224
3x24 Bull Nose	3/8"	NMETAVO3X24BN	NMETCLO3X24BN	NMETGRA3X24BN	NMETTAU3X24BN

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	IV	V3	SCOF - > 0.60 Wet DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

In the field, applying stain to concrete can take a team of laborers hours of prepping, installation and curing time. The Metropolis series presents the modern look of stained concrete in effortless porcelain. The four-shade collection comes in a 12"x24" inch size, along with a 3"x24" inch bullnose. The nonrectified edges add a touch of uniqueness to the installations.

Technical Information

Primary Colors: White, Gray, Beige
Material Type: Porcelain
Finish: Matte

Features At A Glance

- Popular Rectangular Format
- Four Colors in Stained Concrete Look
- Non-Rectified Edges

Trim



3" x 24" Bullnose

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.