

# Incredible 5.0 525 Waterproof Floating Floor

**StoneCast**  
WATERPROOF FLOOR



## Size

7" x 48" nominal (18 cm x 122 cm)  
5.0 mm thick

## Wear Layer

12 mil / UV-Cured Urethane

## Edge Treatment

Four-Sided Microbevel

## Installation

Angle-Angle Click Floating Floor  
(on, above or below grade)

## Attached Cushion

For superior sound abatement  
and easier installation

## Coordinating Moldings

See [nextfloor.net](http://nextfloor.net) for more details.

## Packaging

12 pieces per carton (43 lbs)  
28.4 SF per carton  
55 cartons per pallet  
19 pallets per container

## Testing

|  |             |  |
|--|-------------|--|
| Critical Radiant Flux                        | ASTM E648   | Class I  |
| Surface Flammability                         | DOC FF 1-70 | Passed   |
| Coefficient of Friction                      | ASTM 2047   | Passes>0.6   |
| Static Load Limit                            | ASTM F970   | exceeds 3000 lbs<br><small>without cushion</small> |
| Sound Transmission Class (STC)               | ASTM E90    | 64   |
| Impact Insulation Class (IIC)                | ASTM E492   | 71   |
| High Frequency Impact Insulation Class(HIIC) | ASTM E3222  | 88   |
| Floor Score Certified                        |             |  |
| Phthalate Free                               |             |  |
| 100% Virgin PVC                              |             |  |



## Warranties

Lifetime Waterproof  
Lifetime Residential Wear  
10-Year Commercial Wear\*

\*For moderate traffic areas without rolling loads, heavy  
fixtures or ramps. See full warranty text at [nextfloor.net](http://nextfloor.net)

## Sample SKUs

### Handle Boards

HB525NF-B  
5 per carton (68 lbs)

### Strap Sets

SS525NF-B  
5 per carton (40.7 lbs)

### Step Up Display

8CARDS525NF-1B  
(203, 204, 211, 208)  
8CARDS525NF-2B  
(212, 051, 002, 193)  
FIXT525NF  
Packaged in 3 cartons (128.5 lbs)

