# Monumental 526 & Monumental Plus 570





### Size

526 12" x 24" nominal (30.5 cm x 61 cm)

6 mm total thickness

12" x 36" *nominal* (30.5 cm x 91.44 cm)

6 mm total thickness

#### Wear Layer

20 mil / UV-Cured Urethane

#### **Edge Treatment**

Four-Sided Color-Enhanced Bevel

#### Installation

Angle-Angle Click Floating Floor (on, above or below grade)

# **Attached Cushion**

For superior sound abatement and easier installation.

### **Coordinating Moldings**

See nextfloor.net for more details.

### **Packaging**

526 12 pieces per carton (48 lbs)

24.1 SF per carton 66 cartons per pallet 14 pallets per container

8 pieces per carton (48 lbs)

24.1 SF per carton

54 cartons per pallet

18 pallets per container

#### **Testing**

Critical Radiant Flux Surface Flammability Coefficient of Friction Sound Transmission Class (STC) ASTM E492 65 Impact Insulation Class (IIC)

High Frequency Impact Insulation Class(HIIC) ASTM E3222 92

Static Load Limit Floor Score Certified

100% Virgin PVC

Phthalate Free

ASTM E648 Class I DOC FF 1-70 Passed

ASTM 2047 Passes>0.6

ASTM E989 72

ASTM F970 3000 lbs

## Sample SKUs

**Handle Boards** 

HB526570NF 5 per carton (84.7 lbs)

**Strap Sets** 

SS526570NF

5 per carton (55 lbs)

**Step Up Display** 

4CARDS570NF

(570 011, 041, 104, 106)

4CARDS526NF

(526 002, 602, 604, 601)

FIXT570NF

Packaged in 3 cartons (141 lbs)

**Update Kit** 

4CARDS570NF (570 011, 041, 104, 106)

UPDATEFIX570NF

Packaged in 2 cartons (90 lbs)

### Warranties

Lifetime Waterproof Lifetime Residential Wear Lifetime No Cupping\* 20-Year Commercial Wear†

\*When properly installed; see full warranty text at nextfloor.net

†For moderate traffic areas without rolling loads, heavy fixtures or ramps.



