

Tuscan Sandstone Heavy Commercial Traffic



Size
12" x 24" nominal (31 cm x 62 cm)
2.5 mm thick

Wear Layer
20 mil / UV-Cured Urethane

Edge Treatment
Four-Sided Microbevel

Product Classification
ASTM F1700 Class III, Type B

Installation
Full Spread Adhesive
NEXT 1200™ recommended
With or without grout
Mapei Flexcolor CQ recommended

Coordinating Moldings
See nextfloor.net for more details.

Packaging
21 pieces per carton (39 lbs)
42 SF per carton
54 cartons per pallet
20 pallets per 20ft container

Testing

| | | |
|--|-------------|--------------|
| Critical Radiant Flux | ASTM E648 | Class I |
| Surface Flammability | DOC FF 1-70 | Passed |
| Coefficient of Friction | ASTM 2047 | Passes > 0.6 |
| Static Load Limit | ASTM F970 | 1300 lbs |
| Sound Transmission Class (STC) | ASTM E492 | 64 |
| Impact Insulation Class (IIC) | ASTM E989 | 69 |
| High Frequency Impact Insulation Class(HIIC) | ASTM E3222 | 89 |

Floor Score Certified
Phthalate Free
100% Virgin PVC



Warranties
Lifetime Waterproof
Lifetime Residential Wear
25-Year Commercial Wear*
*See full warranty text at nextfloor.net

Sample SKUs

Handle Boards
HB446NF
5 per carton (48.3 lbs)

Strap Sets
SS446NF
5 per carton (25 lbs)

Folders
3P446NF-C
10 per cartons (39 lbs)

